

SpanSafe® 1000H

Expandable Segregation + Safety Barrier

Function



Strong + Rigid
Construction



Quick + Easy
To Deploy



Weather
Resistant

Features



Smooth Scissor
Type Action



Can Be Locked
With Padlock*



Simple
Installation

Configurations

■ Tube Height:
1000mm

■ Extended Lengths:
From 3m up to 12m

■ Colours Available:
Yellow, Red, White, Custom



Specifications

- Powder coated aluminum tubes
- Steel end poles
- Wall mounted one end, latched one end
- Braked swivel castor on latch end
- Easy to install - wall brackets and anti-luce latch included
- Unique tube connector for long life
- Steel brackets for high wear strength
- Comes pre-assembled
- 3 different heights and multiple colour choices
- Can be securely locked with padlock (*not included)

Product Information

Extended Length x Height	Yellow	Red	White	Custom
3m x 1m	SS10Y3	SS10R3	SS10W3	SS10C3
4m x 1m	SS10Y4	SS10R4	SS10W4	SS10C4
5m x 1m	SS10Y5	SS10R5	SS10W5	SS10C5
6m x 1m	SS10Y6	SS10R6	SS10W6	SS10C6
7m x 1m	SS10Y7	SS10R7	SS10W7	SS10C7
8m x 1m	SS10Y8	SS10R8	SS10W8	SS10C8
9m x 1m	SS10Y9	SS10R9	SS10W9	SS10C9
10m x 1m	SS10Y10	SS10R10	SS10W10	SS10C10
11m x 1m	SS10Y11	SS10R11	SS10W11	SS10C11
12m x 1m	SS10Y12	SS10R12	SS10W12	SS10C12

Detailed Specifications

Application	Pedestrian segregation, safe zones, doorway and gateway access.
Impact	SpanSafe is not recommended for impact situations.
Tube Material	Aluminium 25x25mm SHS - 1.4mm wall thickness
End Pole Material	Mild Steel - 1.6mm wall thickness, zinc plated finish
Bracket Material	Mild Steel - zinc plated, with powder coated finish
Tube Finish	Powder coated to AS/NZS 3715 - Dulux Powder Coat
Colours Available	Standard: Yellow, Red, White. // Special: Blue, Black, Orange, Custom
Tube Length	1000mm
End Pole Height	1280mm
Barrier Height	Closed: 1180mm Extended: 1040mm (Approximate Dimensions Only)
Bottom Gap	167mm
Wall Bracket Length	130mm



NZ Made